

Cemax 460

Grinding Aid and Performance Enhancer

Uses

For use as a Grinding aid Performance Enhancer for the production of Portland and other hydraulic cements.

Description

Cemax 460 is a liquid dispersing agent, for use as a grinding aid and Performance Enhancer for the production of Portland and other hydraulic cements.

Cemax 460 complies with ASTM specification C 465 as a non harmful processing addition. Cemax 460 is a glycol/amine based material.

Properties

Appearance	Liquid Brown
Specific gravity @20°C	1.04 - 1.06
Chloride content	Nil
pH @27°C	10.5 - 11.5

Standards compliance

Complies with ASTM C465.

Application instructions

Dosage

0.03 - 0.07% by weight, depending on type of clinker, type of mill and desired results.

Estimating

Packaging

Cemax 460 is supplied in 200 litre drums.

Storage

Since Cemax 460 has a very low freezing point, no anti-freeze protection is needed in bulk installation. Where it is expected that the storage tanks will be exposed to below zero temperature, provision should be made for insulating and heating the tank and lines in order to prevent excessive viscosity and to aid pumpability.

Shelf life

Cemax 460 has a shelf life of 6 months if kept in a cool and dry place in unopened containers.

Additional information

Health & Safety

Odour, fumes, spillage : No noxious fumes. If accidentally spilled on skin, wash off immediately with soap and water. If accidentally splashed into eyes, wash out immediately with water, and consult a physician. If accidentally swallowed, induce vomiting and call a physician immediately.

Cemax 460



Fosroc Chemicals (India) Pvt. Ltd.

Head Office

Embassy Point, No. 150,
2nd Floor, Infantry Road,
Bangalore 560 001,
Karnataka

Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

telephone

+91 80-42521900

fax

+91 80-22281510

e-mail

enquiry.india@fosroc.com

Regional Offices

Chennai

Hills Centre, Old No 5,
New No 9, 3rd Cross Street,
Jeth Nagar, Raja Annamalaipuram,
Chennai 600 028.
Ph: 9500064795

Mumbai

MBC Park, 12th floor, Office No.12B,
'D' Block, Near G Corp/Hyper City
Kasarwadawali, Ghodbunder Road,
Thane (West) 400 615
Ph: +91 22 6229 6800

Noida

Unit No. 601, Highway Tower-II
A-13/2, 6th Floor, Sector- 62
Gautam Buddha Nagar,
Noida 201 309, Uttar Pradesh
Ph: +91 120 6121900
Fax: 0120-4270622

Kolkata

304, Jodhpur Park
Kolkata 700 068
Ph: +91 33-65343188
Fax: 033-2499-0278

www.fosroc.com