

PRODUCT DATA SHEET

Sika[®]-1

INTEGRAL WATERPROOFING ADMIXTURE

DESCRIPTION

Sika[®]-1 is a normal setting liquid waterproofing admixture for mortar and concrete. Suitable for use in hot and tropical climatic conditions.

USES

Sika[®]-1 is used for waterproofing of mortars and concrete, in particular for:

- Renders, masonry mortars and screeds
- Reinforced and unreinforced concrete
- Brick, concrete and stone substrates
- Indoor and outdoor applications, such as basements, swimming pools, tunnels, water tanks, manholes, culverts

FEATURES

Sika[®]-1 blocks the capillaries and pores in the applied cementitious system to provide an effective water barrier against the transmission of liquid water. The benefits of Sika[®]-1 include, but are not limited to the following:

- Increased impermeability of mortar/concrete
- Ready to use
- Easily dispersed
- Chloride-free

PRODUCT INFORMATION

Composition	Blend of silicates
Packaging	20 L can and 200 L drum
Shelf life	12 months from date of production if stored properly in undamaged, unopened, original sealed packaging.
Storage conditions	Storage at temperatures between 5 °C and 30 °C. Protect from direct sunlight, frost and contamination.
Appearance and colour	White liquid
Density	~1.02 kg/l
Total chloride ion content	Nil

APPLICATION INFORMATION

Recommended dosage Add one part of Sika[®]-1 to 10 parts of water, which is equivalent to approximately 3 % of cement content. When using very wet sand, the ratio must be increased to 1:8 or in extreme cases 1:6.
Note: Trial mixes should always be conducted to establish the exact dosage rates and water requirements per mix.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

Sika®-1 must be stirred slowly before use to ensure a homogeneous, lump free consistency. Sika®-1 shall be diluted in the gauging water. The dilution must be stirred slowly (to ensure a homogeneous, lump free consistency) prior addition into the mortar/concrete mixer. Sika®-1 can also be added neat to the mortar/concrete mix provided that the mixture is properly mixed to achieve a homogeneous consistency.

APPLICATION METHOD / TOOLS

The standard rules of good concreting practice (concerning production, placing and curing) are to be followed. Refer to relevant standards.

Sika®-1 may be combined with many other Sika® products.

Note: Preliminary testing is required to prove the compatibility. Please contact Sika technical service for more information and advice.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Gulf B.S.C. (c)

Tel: +973 177 38188

Email: info@bh.sika.com

Sika Kuwait Cons. Mat. & Paints Co WLL

Tel: +965 22 282 296

Email: sika.kuwait@kw.sika.com

Web: gcc.sika.com

Sika UAE LLC

Sika MB Construction Chemicals LLC

Sika International Chemicals LLC

Tel: +971 4 439 8200

Email: info@ae.sika.com

Web: gcc.sika.com

Sika Saudi Arabia Limited

Riyadh / Jeddah / Dammam / Rabigh

Tel: +966 11 217 6532

Email: info@sa.sika.com

Web: gcc.sika.com

Sika LLC - Oman

Master Builders Solutions LLC

(part of Sika)

Tel. +968 22 826 500

Email: info@om.sika.com

Web: gcc.sika.com



ISO 9001, 14001, 45001 – SGS
- Sika UAE LLC
- Sika International Chemicals LLC
- Sika Gulf B.S.C. (c)
ISO 9001, 14001 – SGS
- Sika Saudi Arabia Limited
ISO 9001, 14001 – TÜV
- Sika MB Construction Chemicals LLC
- Master Builders Solutions LLC

All products are supplied under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.



Product Data Sheet

Sika®-1

March 2024, Version 01.03

020705040010000001

Sika-1-en-AE-(03-2024)-1-3.pdf

