



Acryrub PRO+

Description

Acryrub PRO+ is an all-in-one painter's kit for indoor applications. Acryrub PRO+ is a one component, paintable, plasto-elastic sealant based upon acrylic dispersion.

Properties

- Easy to apply
- Colorfast and waterproof after curing
- Crack-free
- Can be painted with water-based systems
- Very good adhesion on many porous surfaces, aluminum & PVC

Applications

- Joints with movements upto 12.5%.
- Connection joints in the building industry.
- Joints in windowsills, between brickwork, etc.



Technical data

| | |
|--------------------------------|--------------------|
| Base | Acrylic Dispersion |
| Consistency | Paste |
| Curing system | Physical Drying |
| Specific Gravity (g/ml) | 1.67 ± 0.05 |
| Skin formation (minutes) | ~ 20 |
| Shrinkage (%) | DIN 52451 ~ 15 |
| Maximum allowed Distortion (%) | ca. 12 |
| Temperature Resistance (°C) | -20 to +80 |
| Application Temperature (°C) | +5 to +30 |

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrate

Substrates

- Substrate condition
The surface must be rigid, clean, dry, free of dust and grease.
- Substrate preparation
Highly porous surfaces should be primed with diluted Acryrub PRO+ (1 part Acryrub PRO+ and 2 parts water).
- Substrate types
Acryrub PRO+ has a good adhesion to all common porous building substrates.
Acryrub PRO+ has no good adhesion or is not suitable for PE, PP, PTFE (Teflon®), bituminous substrates, copper or copper containing materials such as bronze and brass.

We recommend a preliminary adhesion test on every surface.



Acryrub PRO+

Application method

- Application method
Apply the product with a manual, pneumatic or a battery-operated caulking gun.
- Cleaning method
Before curing, Acryrub PRO+ can be removed with water from substrates and tools. Cured sealant must be removed mechanically.
- Finishing method
Finish with a spatula or putty knife.
- Repair method
Repair with the same material.

Joint Size

Minimum Width: 5 mm
Maximum Width: 20 mm
Minimum Depth: 5 mm
Recommendation for sealing jobs: Joint Depth = Joint Width

Use PE backer rods in case of large joint dimensions to avoid three-point adhesion.

Health and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.
Dangerous. Respect the precautions for use.

Packaging/Logistics

Colour: White
Packaging: 450g Cartridge, 450g Sausage
Shelf life: 12 months from the date of production. The product must be stored in its original, undamaged, and sealed packaging under dry conditions, protected from direct sunlight, and at temperatures between +5°C and +25°C.

Remarks

- Do not use in applications where continuous water immersion is possible.
- Paintable with most paints, However given the great diversity in available paints, it is recommended to do a compatibility test prior to the application.
- Do not apply when rain or frost is imminent.
- The paint should be sufficiently elastic to be applied on a plasto-elastic sealant. A preliminary test is recommended to prevent cracking.
- With the expanding range of coatings used in the fenestration industry, sealant compatibility with specific coating systems must be verified; therefore, a preliminary adhesion test is recommended prior to application.

This technical data sheet supersedes all earlier versions. The information provided is based on our tests and practical experience and is supplied in good faith as general guidance only, without creating any liability. Since materials, substrates, application design, and processing conditions vary widely and are outside our control, we cannot accept responsibility for the results obtained from use of this information. The user must verify suitability for the intended application through their own testing, and preliminary trials are recommended in all cases. The manufacturer reserves the right to change product specifications without prior notice.