

ShaliKote® DPC

Economic Elastomeric Asphalt Emulsion Liquid Membrane



Description

ShaliKote® DPC is an elastomeric, liquid applied, emulsified polymerized asphalt membrane designed for damp-proofing of concrete structures of below & above ground levels.

Characteristics - Physical

Appearance	Viscous brownish emulsion dries to black coating	Drying time, hrs.	24*
Specific Gravity @ 30°C	1.02 ± 0.02	Application Condition	Not to be used < 5°C or RH > 85%**
Solid content (%)	35 ± 5	Theoretical coverage in 2 coats, m ² / ltr [ft ² / ltr]	2 to 2.75 [22 to 30]#

* Depends upon the surface temperature, RH & climate condition.

** If it is applied below 5°C or relative humidity >85%, film formation time will be higher.

Depends upon the surface condition.

Application

- Damp-proofing of concrete and masonry structures.
- Moisture barrier damp-proof course over plinth coping.
- Subgrade concrete and metal substrate.

Advantages

- Water based product, cleaner technology, non-toxic.
- Easy to apply by brush and roller.
- Cold applied material.
- Excellent impermeability.
- Good flexibility and does not crack on aging.
- Seamless elastomeric membrane.
- Can be applied over damp surface.

Application Methodology

➤ Surface Preparation

- Ensure that surface is free from all loose gravel, dirt and foreign matter with high-pressure wash. Before application surface should be totally dry, free from moisture, oil, grease, mill scale or dust.

➤ Priming

- Prime the surface after thoroughly mixing 4 parts of **ShaliKote® DPC** with 1 part of potable water, by brush or roller or airless spray. Slightly damp surface will help in the brushing application.
- Allow it to dry completely before application of the **ShaliKote® DPC**.

➤ Application of material

- Apply **ShaliKote® DPC** by brush / roller on primed surface @ 0.25 liter / m² as first coat.
- Allow the first coat to dry and apply second coat of **ShaliKote® DPC** @ 0.25 liter / m² in a direction perpendicular to the first. An optional third coat after drying of the previous may be applied.
- Overall coverage shall depend on application and surface finish of substrate.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapor.
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash immediately with plenty of clean water and seek medical advice.
- If swallowed seek medical attention immediately. Do not induce vomiting.

Packing

Available in 5 liter and 20 liter pack.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



- Product Range**
- Waterproofing & Insulation
 - Road Surfacing
 - Sealants & Adhesives
 - Pipeline Coatings
 - Protective/Anti-Corrosion Coatings
 - Epoxy and Flooring
 - Grouts and Admixtures (GARA)
 - RestoFix - Repair/Rehabilitation
 - Other Construction Chemicals



Advisory Cell: +91 81302 81114

www.stpltd.com

250702